



Granulats : 16/22.4 roulé
Pétrographie : Alluvionaire silico-calcaire

Partie contractuelle
Valeurs spécifiées sur lesquelles le producteur s'engage

Classe granulaire			Norme											Catégorie				
16	22.4	Norme XP P 18-545 Article 10 - EN 12620 et EN 13139											Code A					
		d/2					d				D			1.4D	2D			
	0.063	8	10	12.5	14	16	18	20	22.4	25	31.5	45	f	FI	W			
Etendue e						15			15									
V.S.S.+U	2.1	6				25			100					24.00				
V.S.S.	1.5	5				20			96				1.50	20.00				
V.S.I.		0				5			81		98	100						
V.S.I.-U		0				0			76		97							

Partie informative
Résultats de production

du 13/01/25 au 27/10/25															
	0.063	8	10	12.5	14	16	18	20	22.4	25	31.5	45	f	FI	W
Maximum	0.0	0	1	4	10	20	52	76	93	99	100	100	0.05	18.65	1.8
Xf+1.25xEcart-types	0.0	0	1	4	9	20	48	73	90	99	100	100	0.04		1.7
Moyenne Xf	0.0	0	0	2	5	14	37	61	85	97	100	100	0.02	15.80	1.3
Xf-1.25xEcart-types	0.0	0	0	0	1	8	25	49	79	95	100	100	0.00		0.9
Minimum	0.0	0	0	0	1	8	24	46	81	94	100	100	0.00	9.59	0.4
Ecart-type	0.01	0.1	0.2	1.3	3.1	4.6	9.0	9.6	4.4	1.4	0.0	0.0	0.013	2.923	0.30

